

## Keeps tight: New adjustment technology for concealed entrance door hinge from BaSys

The „Masterband FX2 120 3-D CS“ is undergoing a radical change. Basys also shifts the side gap adjustment of the three-dimensionally adjustable hinge into the frame part. As a result, the tightness of exterior doors, which are particularly exposed to weathering and temperature fluctuations, is no longer negatively affected during adjustment.

At BAU 2015, the company presented with the „Masterband FX2 120 3-D CS“ for the first time a concealed door hinge for rebated entrance doors with 18 mm overlap and continuous seal in the leaf. When adjusting the side gap with a margin of plus/minus three millimetres, however, the seal in the leaf was sometimes displaced – with negative effects on the tightness which is essential for front doors.

Basys recognized the potential for optimization and shifted the side gap adjustment. In the new model, all three dimensions of adjustment – including the height adjustment and the pressure of the seal – are now located in the frame part of the hinge. The leaf part and the continuous seal enclosed by the hinge remain untouched during adjustment. Seen from the outside and with the door closed, the hinge remains concealed.

The optimized model replaces the existing one. Only the cut-out in the door frame needs to be recessed from 21 to 25 millimeters. The external dimensions and contours of the hinge remain the same.

In the category „Excellent Product Design – Building and Elements“ the “ Masterband FX2 120 3-D CS “ has already received one of the coveted „Winner“ awards at the German Design Award. It has a load-bearing capacity of 120 kilograms per pair, maintenance-free bearings and three-dimensional adjustment – recently without any negative effects on the tightness of the front door.



*Caption 1: In the old model of the "Masterband FX2 120 3-D FD", the side gap adjustment was still in the leaf of the concealed hinge developed for front doors. When adjusting the side gap, however, the seal in the leaf was sometimes displaced - with negative effects on the tightness which is essential for front doors. Photo: BaSys*



*Caption 2: In the new model of the "Masterband FX2 120 3-D FD", all three dimensions of adjustment - the side gap adjustment, the height adjustment and the pressure of the seal - are now located in the frame part of the hinge. The leaf part and the continuous seal enclosed by the hinge remain untouched during adjustment. Photo: BaSys*



*Caption 3: The "Masterband FX2 120 3-D FD" has already received one of the coveted "Winner" awards at the German Design Award. It has a load-bearing capacity of 120 kilograms per pair, maintenance-free bearings and three-dimensional adjustment - recently without any negative effects on the tightness of the front door. Photo: BaSys*

## BaSys

BaSys stands for Bartels Systembeschläge. The family-owned company run by Albert and Jürgen Bartels has been developing, producing and selling an all-embracing range of building hardware since 1995. With its hinge and striking-plate systems, BaSys regards itself as a problem solver for door and frame manufacturers throughout Europe as well as for national and international customers from retail and the trades. In 2001, the company was the first German manufacturer to present a concealed and three-dimensionally adjustable hinge with the "Pivota" product range, initiating a new design trend in the door industry. At company headquarters in Kalletal, East Westphalia, BaSys employs around 100 members of staff.